



PRV INSPECTION AND TEST REPORT

BRANCH: Fort St John

UVL ID#: 14548F

Work Order: 308644

Customer PO#:

Customer: CANADIAN NATURAL RESOURCES LIMITED

Date: 09/05/2012

Facility: BUCKINGHORSE

LSD: d-044-A/94-G-10

PSV Location: SALES DEHY CONTACTOR

A#: A0491894

Vessel SN: 02-3854-1

Cust Id: FSJ 3703

Cust. Ref.:

Valve PO:

PO LINE#:

Cust. WO#:

Cust AFE#:

Cost Centre#: 81016478

VALVE DATA

Man.: FARRIS Model: 26HA13-120 Serial: 452734-1-A10 Seat: POP
Conn. Flanged Inlet: 2" 600 RF Orifice: H Outlet: 3" 150 RF
Set Press. 1410 PSI Back Press.: 0 PSI Cold/Diff Set Press: Temp: Cap: 21497 SCFM
Lift Lever [ ] Cap Assembly: Closed Code Symbol: UV CRN#: 0G2369.5C

CUSTOMER INSTRUCTIONS

Instructions: Pretest, Service, and Test Pretest Required? [x] Reset Required? [ ]
Replaces UVL ID#: Replaces Valve Serial#: Replaces Valve Cust ID#
RESET INFO: New Pressure: New Cold/Diff Set: New Capacity: New Model:

CONDITION AS RECEIVED

Visual Condition: Good Data Plate Condition: OK Date of last service: 6/09
Seal Condition: Top: Intact Bottom: Intact Insignia: UVL Fittings Attached: Inlet: [ ] Outlet: [ ]
Inlet: Carbon Inlet Plugged: [ ] Outlet: Oily Outlet Plugged: [ ] Initial Insp. Signoff: Tara Stones

PRETEST 1

Simmer: 1421 PSI Set Press: 1423 PSI Rseat: 1323 PSI Leakage: 60+ BPM Test Gauge: FSJ 1&2
Tested By: Harley Anderson Pretest Comments:

PRETEST 2

Simmer: PSI Set Press: PSI Rseat: PSI Leakage: BPM Test Gauge:
Tested By: Pretest Comments:

COMPONENTS INSPECTION

Table with columns: ITEM, CLEAN, OILY, RUSTY, CARBON, OTHER, COMMENTS, OK / REPLACED, REPLACED?, REPAIRS PERFORMED. Rows include DISC, NOZZLE, CAP-LEVER ASSY, COMP SCREW and LOCKNUT, SPRING and BUTTONS, SPINDLE / STEM, STEM RETAINER, DISC HOLDER, GUIDE / UPPER RING, LOWER RING, RING PIN(S), BELLOWS, GASKET / SEALS, CONNECTION ENDS, OTHER.

DISC: : 0.296 ACT - 0.314 NOZZLE: MIN - 5.031 ACT - 5.119 NUMBER: HG2122CR

Comments:

Disassembly: BRANDON KATAQUAPIT Inspection: BRANDON KATAQUAPIT Reassembly: BRANDON KATAQUAPIT

FINAL TEST

Test Medium: Air Simmer: 1408 PSI Set Pressure: 1410 PSI
Rseat: 1311 PSI Leakage: 0 BPM B.P. Test: 60 PSI Cold/Diff Set: PSI
ADJ. RING SETTING (NOTCHES): Upper: N/A Lower: -1 Test Gauge: FSJ 1&2 Set Press Def: POP
Tested by:

FINAL INSPECTION:

SEAL: Top: [x] Bottom: [x] End Protectors Installed: [x] Painted: [x] Palletized: [x] Ship Container: [ ] Flex Gaskets Supplied: [x]
Final Inspection: Tara Stones Customer Inspection:
Comments: