



PRV INSPECTION AND TEST REPORT

BRANCH: Fort St John

UVL ID#: 8942F

Work Order: 307836

Customer PO#:

Customer: CANADIAN NATURAL RESOURCES LIMITED
Facility: KOBES
A#: A476352
Cust. Ref.: FSJ 4890
Cust. WO#:

LSD: a-017-J/94-B-09
Vessel SN: N/A
Valve PO:
Cust AFE#:

Date: 11/22/2011
PSV Location: INLET SEPERATOR
Cust Id: CRN K1906-12
PO LINE#:
Cost Centre#:

VALVE DATA

Man.: FARRIS Model: 26FA13-120 Serial: 439048-5-A10 Seat: POP
Conn. Flanged Inlet: 1.5" 600 RF Orifice: F Outlet: 2" 150 RF
Set Press. 1375 PSI Back Press.: 0 PSI Cold/Diff Set Press: Temp: Cap: 8911 SCFM
Lift Lever Cap Assembly: Closed Code Symbol: UV CRN#: 0G2369.5C

CUSTOMER INSTRUCTIONS

Instructions: Pretest, Service, and Test Pretest Required? [checked] Reset Required? [ ]
Replaces UVL ID#: Replaces Valve Serial#: Replaces Valve Cust ID#
RESET INFO: New Pressure: New Cold/Diff Set: New Capacity: New Model:

CONDITION AS RECEIVED

Visual Condition: Good Data Plate Condition: OK Date of last service: 6/08
Seal Condition: Top: Intact Bottom: Intact Insignia: UVL Fittings Attached: Inlet: [ ] Outlet: [ ]
Inlet: Clean Inlet Plugged: [ ] Outlet: Clean Outlet Plugged: [ ] Initial Insp. Signoff: Tara Stones

PRETEST 1

Simmer: 1381 PSI Set Press: 1382 PSI Reseat: 1285 PSI Leakage: 40+ BPM Test Gauge: FSJ 1+2
Tested By: Harley Anderson Pretest Comments:

PRETEST 2

Simmer: PSI Set Press: PSI Reseat: PSI Leakage: BPM Test Gauge:
Tested By: Pretest Comments:

COMPONENTS INSPECTION

Table with columns: ITEM, CLEAN, OILY, RUSTY, CARBON, OTHER, COMMENTS, OK / REPLACED, REPLACED?, REPAIRS PERFORMED. Rows include DISC, NOZZLE, CAP-LEVER ASSY, COMP SCREW and LOCKNUT, SPRING and BUTTONS, SPINDLE / STEM, STEM RETAINER, DISC HOLDER, GUIDE / UPPER RING, LOWER RING, RING PIN(S), BELLOWS, GASKET / SEALS, CONNECTION ENDS, OTHER.

DISC: Min: .265 ACT - .285 NOZZLE: MIN - 4.375 ACT - 4.463 NUMBER: HG2017CR

Comments:

Disassembly: Brian Gunson Inspection: Brian Gunson Reassembly: Brian Gunson

FINAL TEST

Test Medium: Air Simmer: 1373 PSI Set Pressure: 3175 PSI
Reseat: 1270 PSI Leakage: 10 BPM B.P. Test: 60 PSI Cold/Diff Set: PSI
ADJ. RING SETTING (NOTCHES): Upper: N/A Lower: -10 Test Gauge: FSJ 1+2 Set Press Def: POP
Tested by:

FINAL INSPECTION:

SEAL: Top: [checked] Bottom: [checked] End Protectors Installed: [checked] Painted: [checked] Palletized: [checked] Ship Container: [ ] Flex Gaskets Supplied: [checked]

Final Inspection: Tara Stones Customer Inspection:

Comments: