



PSV
 located top middle of vessel
 Serviced - 01/10/2008
 By Unified Valve
 ID 291368
 SN 438952-1-A10
 Mem - Farnis
 Set press 270 psi Cap 1076 sqm
 Size 2x3" Flanged
 Model - 76HA12-120

- paint in good shape
 - no visible flange leaks
 - temp & pressure gauges inboard and in good shape
 - all flange bolts - tight, in place

CUSTOMER: CNRL FACILITY: ETZIKOM Compressor Station LSD: 08-24-006-10w4M
 P & ID: _____ DRAWN BY: A Gemmell DATE: 07Apr09 DRAWING NO. _____
VESSEL INFORMATION:
 Equip. No. _____ Pro.Reg.No (A) A0496494 C.R.N. R4179.2 Serial No. C2033A.HS Yr. Inst. _____
 Code/Div. _____ Size: 48" ID 40Dx Manufacturer: Rushton Gas & Oil Equip Yr. Blt. 2003
 C. Stamp 70 Service: _____ PWHT: _____ J.E.: _____ Radiography: RT-2 Insulated: no
HEAD:
 Top Mat'l _____ Top Nom. 1.125" Top C.A. _____ SHELL: Material _____ Nominal 1.250" C.A. .0625"
 Btm Mat'l _____ Btm Nom. _____ Btm C.A. _____
BOOT:
 Head Mat'l _____ Head Nom. _____ Head C.A. _____ CHANNEL: Top Mat'l _____ Top Nom. _____ Top C.A. _____
 Shell Mat'l _____ Shell Nom. _____ Shell C.A. _____ Btm Mat'l _____ Btm Nom. _____ Btm C.A. _____
 MAWP Shell side: 4964 kpa @ Temp. 54c MAWP Tube Side: _____ @ Temp. _____
PIPING INFORMATION:
 Circuit. No. _____ Line No. (s) (PLEASE PUT LINE NUMBERS ON APPLICABLE LINES ON THE DRAWING)
 Piping Class _____ Service: _____ Yr. Blt. _____
 MAWP: _____ @ Temp. _____ Size & Schedule of Piping (PLEASE PUT APPROPRIATE SIZES AND SCHEDULES OF PIPING ON DRAWING)

A0496494 UT Readings

Readings in inches

LOC 5	1.275	1.317	1.280
LOC 10	1.284	1.285	1.284
LOC 15	1.285	1.285	1.285
LOC 20	1.281	1.282	1.281
LOC 25	1.277	1.301	1.290
LOC 30	0.227	0.230	0.229
LOC 35	0.580	0.592	0.588
LOC 40	0.355	0.369	0.360
LOC 45	0.615	0.620	0.617
LOC 50	0.346	0.359	0.356
LOC 55	0.313	0.325	0.315
LOC 60	0.355	0.364	0.361
LOC 65	1.288	1.293	1.288