



PRV INSPECTION AND TEST REPORT

BRANCH: Fort St John

UVL ID#: 8579F

Work Order: 308562

Customer PO#:

Customer: CANADIAN NATURAL RESOURCES LIMITED

Date: 8/8/2012

Facility: CARIBOU

LSD: d-062-C/94-A-16

PSV Location: DEHY TOWER

A#: A3098592

Vessel SN:

Cust Id:

Cust. Ref.: BLUE TAG-8579F

Valve PO:

PO Line#:

Cust WO#:

Cust AFE#:

Cost Centre #:

VALVE DATA

Man.: FARRIS

Model: 26EA13-120

Serial: 459060-3-A10

Seat: Hard

Conn: Flanged

Inlet: 1 " 600RF

Orifice: E

Outlet: 2 " 150RF

Set Pres: 1440 PSI

Back Press: 0 PSI

Cold/Diff Set: PSI

Temp:

Cap: 5657 SCFM

Lift Lever:

Cap Assembly: Closed

Code Symbol: UV

CRN#: 0G8442.5C

CUSTOMER INSTRUCTIONS

Instructions: Pretest, Service, and Test

Pretest Required?

Reset Required?

Replaces UVL ID#:

Replaces Serial #:

Replaces Cust ID#:

RESET INFO: New Pressure:

New Cold/Diff:

New Capacity:

New Model:

CONDITION AS RECEIVED

Visual Condition: Good

Data Plate Condition: OK

Date of last service: 5/07

Seal Condition: Top: Intact

Bottom: Intact

Insignia: UVL

Fittings Attached: Inlet:  Outlet:

Inlet: Carbon

Inlet Plugged:

Outlet: Oily

Outlet Plugged:

Initial Insp. Signoff: Tara Stones

PRETEST 1

Simmer: 1438 PSI Set Press: 1440 PSI Reseat: 1280 PSI Leakage: 50 BPM Test gauge: FSJ 1&2

Tested by: Brian Gunson

Pretest comments:

PRETEST 2

Simmer: PSI Set Press: PSI Reseat: PSI Leakage: BPM Test gauge:

Tested by:

Pretest comments:

ITEM	CLEAN	OILY	RUSTY	CARBON	OTHER	COMMENTS	OK / REPLACE	REPLACED?	REPAIRS PERFORMED
DISC	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Pitted	OK	<input type="checkbox"/>	Machine/Lap/Polish
NOZZLE	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Pitted	OK	<input type="checkbox"/>	Machine/Lap/Polish
CAP-LEVER ASSY	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		OK	<input type="checkbox"/>	
COMP SCREW and LOCKNUT	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		OK	<input type="checkbox"/>	
SPRING and BUTTONS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		OK	<input type="checkbox"/>	
SPINDLE / STEM	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		OK	<input type="checkbox"/>	
STEM RETAINER	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Galled	REPLACE	<input checked="" type="checkbox"/>	303768X1-010
DISC HOLDER	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		OK	<input type="checkbox"/>	
GUIDE / UPPER RING	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Galled	REPLACE	<input checked="" type="checkbox"/>	304181X11-010
LOWER RING	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		OK	<input type="checkbox"/>	
RING PIN(S)	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		OK	<input type="checkbox"/>	
BELLOWS	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	N/A		<input type="checkbox"/>	
GASKET / SEALS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Crushed	REPLACE	<input checked="" type="checkbox"/>	
CONNECTION ENDS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		OK	<input type="checkbox"/>	
OTHER	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			<input type="checkbox"/>	

Disc: MIN= .234 ACT= .248 Nozzle: : 4.062 ACT= 4.117 Spring Number: N/A

Comments:

Disassembly: Brian Gunson

Inspection: Brian Gunson

Reassembly: Brian Gunson

FINAL TEST:

Test Medium: Air Simmer: 1435 PSI Set Pressure: 1440 PSI

Reseat: 1287 PSI Leakage Acceptable:  B.P. Test: 60 PSI

ADJ. RING SETTING (NOTCHES): Upper: N/A Lower: -7 Test Gauge FSJ 1&2 Set Press Def: POP

Tested by: Harley Anderson

FINAL INSPECTION:

SEAL: Top:  Bottom:  End Protectors Installed:  Painted:  Palletized:  Ship Container:  Flex Gaskets Supplied:

Final Inspection: Tara Stones

Customer Inspection

Comments: