



Mothballing and Rendering Safe Documentation Form

TC-OVR-FM-INT-000046_2

Equipment Description

Jur #:	A491800	Date:	Oct 2022
Serial #:	020381201	Facility:	Townsend
Equipment Type:	<input checked="" type="checkbox"/> Vessel <input type="checkbox"/> Piping <input type="checkbox"/> Tank <input type="checkbox"/> Other	Equipment Number:	V.200
Equipment Description:	contactos	Equipment LSD/NTS:	A-17.5/94.6.9

If mothballing or rendering safe multiple pieces of equipment insert "See Attached List"

Mothballing for Temporary Suspension of Operation (<12 months)

- 1) The equipment will remain out-of-service for **less than 12 months**
- 2) Mothballing required actions will be carried out as per Section 4 of [TC-OVR-PRO-INT-000021](#)
- 3) Equipment Inspection and PRD servicing not required but maintained at given frequencies
- 4) Equipment status remains "in-service", form required in IDMS to document layup process

Mothballing for Temporary Suspension of Operation (>12 months)

- 1) The equipment will remain out-of-service for **more than 12 months**
- 2) Mothballing required actions will be carried out as per Section 5 of [TC-OVR-PRO-INT-000021](#)
- 3) Equipment Inspection and PRD servicing is required when returned to active operation
- 4) Equipment status changed to "out of service", form is required in IDMS to track changes

Mothballing for Surplus (To be relocated)

- 1) The equipment will be allocated for surplus based on the Shut-In Facility Management Guideline - Guide for transitioning Active Facility to Shut-in Status (Field OPS)
- 2) Mothballing required actions will be carried out as per Section 5 of [TC-OVR-PRO-INT-000021](#)
- 3) Equipment status changed to "mothballed", form is required in IDMS to track changes

Rendering Safe for Decommissioning

- 1) The equipment has been selected for decommissioning as per the Shut-In Facility Management Guideline - Guide for transitioning Active Facility to Shut-in Status (Field OPS)
- 2) Rendering Safe required actions will be carried out as per Section 7 of [TC-OVR-PRO-INT-000021](#) and the