



- V-300: GLYCOL HEAT EXCHANGER, 1687 x 1147 x 3050 LG, (10 TRAY), 80.6% E.F., 86.27 HP, 6.7% C.P., 3.32% (TOP PHASE PLUGGED) C/A
- H-101: BUILDING HEATER, CATAPANE 12,000 BTU/HR, 110 WAC
- P-300 A/B: GLYCOL PUMP, MINWAY 2102 P, CAPACITY: 210 GPM
- Y-301: GLYCOL FILTER, NOMATA 152C H.P. CARTRIDGE FILTER HOUSING, 4.1" x 15.8" H.G.E.
- Y-302: CHARCOAL FILTER, WELLS-HALL #2.50 TWO CARTRIDGE, 5.1" x 14.8" H.G.E.
- E-302: AIR/GLYCOL EXCHANGER, 300,000 BTU/HR, 4.05' O.D. x 35.5' LG, 4" TRUNK PIPING, c/w 300,000 BTU/HR FLAME ARRESTOR
- E-303: GAS/GLYCOL HEAT EXCHANGER, 1687 x 1147 x 3050 LG
- V-301: FUEL GAS ACCUMULATOR, SET @ 112.5 MPa, 40.2" C.A., 1.59mm
- H-302: FUEL GAS PREHEAT, 300,000 BTU/HR, 30.5" O.D. x 35.5' LG, 4" TRUNK PIPING, c/w 300,000 BTU/HR FLAME ARRESTOR
- Y-302: CARBOHYDRATE REGENERATOR, 300,000 BTU/HR, 4.05' O.D. x 35.5' LG, 4" TRUNK PIPING, c/w 300,000 BTU/HR FLAME ARRESTOR