



Equip. No. _____ Prov. Reg. No. Ⓐ C 36020 C.R.N. NON CODE Serial No. 3856-A Yr. Inst. _____
 Code/Div. NON CODE Size: 60in x 20ft Manufacturer: ARGO SALES Yr. Blt. 2006
 C. Stamp: N/S Service: SOUR PWHT: NIL Radiography: NIL Insulated: YES

Design & Materials Data

HEAD:
 Top Mat'l. SA 36 Top Nom. 9.5mm Top C.A. 1.6mm
 Btm. Mat'l. _____ Btm. Nom. _____ Btm. C.A. _____
 CHANNEL:
 Material: _____ Nominal: _____ C.A. _____
 BOOT
 Head Mat'l. _____ Head Nom. _____ Head C.A. _____
 Shell Mat'l. _____ Shell Nom. _____ Shell C.A. _____
 SHELL
 Material: SA 36 Nominal: 9.5mm C.A. 1.6mm
 MAWP Shell Side: 103 kPa @ Temp. 38°C
 MAWP Tube Side: _____ @ Temp. _____

CLIENT	CANADIAN NATURAL RESOURCES	
FACILITY	HALFWAY BATTERY LSD 05-12-87-25 W6M	
ITEM	LOW PRESSURE KNOCKOUT DRUM	
BY: JE	DATE: 04/2008	DWG.# 37A

UTS DATA

CLIENT: CANADIAN NATURAL RESOURCES
EQUIPMENT: L.P. FLARE KNOCK OUT DRUM
CRN#:
PROV REG: C 36020
TESTED ON STREAM

FACILITY: HALFWAY BATTERY
SERVICE: SOUR
LOCATION: 05-12-87-25 W6M
RTD JOB #: 05.001616
REFER TO DRAWING: 37A

Test Point	THICKNESS DATA				Flag	Crit	C.A.	Nom.	Short Term	Long Term	Ave. mm/py	Flag Date
5												
Description:	BOTTOM SHELL											
	2008 4											
Min. Thick.	9.6	0	1.6	9.5					0	0		L
Average:	9.7											L
Analysis:												
10												
Description:	BOTTOM SHELL											
	2008 4											
Min. Thick.	9.5	0	1.6	9.5					0	0		L
Average:	9.6											L
Analysis:												
15												
Description:	BOTTOM SHELL											
	2008 4											
Min. Thick.	9.5	0	1.6	9.5					0	0		L
Average:	9.6											L
Analysis:												
20												
Description:	2" 90° ELBOW											
	2008 4											
Min. Thick.	4.9	4.8	.7	5.5					0	0		L
Average:	5											L
Analysis:												