

UTS DATA

CLIENT: CANADIAN NATURAL RESOURCES
EQUIPMENT: SEPARATOR
CRN#: M-7382.231
PROV REG: A 434522
TESTED ON STREAM

FACILITY: KNOPCIK GAS GATHERING
SERVICE: SWEET
LOCATION: 05-19-72-10 W6M
RTD JOB #: 05.004259
REFER TO DRAWING: 47

Test Point	THICKNESS DATA				Flag	Crit	C.A.	Nom.	Short Term	Long Term	Ave. mm/py	Flag Date
115												
Description:	UPPER SHELL											
	2010 3											
Min. Thick.	28.8	25.4	3.2	28.6					0	0		L
Average:	28.9											L
Analysis:												
120												
Description:	MID SHELL											
	2010 3											
Min. Thick.	29	25.4	3.2	28.6					0	0		L
Average:	29											L
Analysis:												
125												
Description:	LOWER SHELL											
	2010 3											
Min. Thick.	29	25.4	3.2	28.6					0	0		L
Average:	29.1											L
Analysis:												
130												
Description:	2" CIRC BAND											
	2010 3											
Min. Thick.	8.5	7.6	1.1	8.7					0	0		L
Average:	8.8											L
Analysis:												

UTS DATA

CLIENT: CANADIAN NATURAL RESOURCES
EQUIPMENT: SEPARATOR PIPING
CRN#:
PROV REG:
TESTED ON STREAM

FACILITY: KNOPCIK GAS GATHERING
SERVICE: SWEET
LOCATION: 05-19-72-10 W6M
RTD JOB #: 05.004259
REFER TO DRAWING: 47

Test Point	THICKNESS DATA				Flag	Crit	C.A.	Nom.	Short Term	Long Term	Ave. mm/py	Flag Date
105												
Description:	3" 90° ELBOW											
	2010 3											
Min. Thick.	6.7	6.65	1	7.6					0	0		L
Average:	6.9											L
Analysis:												
110												
Description:	4" 90° ELBOW											
	2010 3											
Min. Thick.	5.6	5.25	.8	6					0	0		L
Average:	5.8											L
Analysis:												
135												
Description:	4" 90° ELBOW											
	2010 3											
Min. Thick.	5.9	5.25	.8	6					0	0		L
Average:	6											L
Analysis:												
140												
Description:	4" 90° ELBOW											
	2010 3											
Min. Thick.	5.7	5.25	.8	6					0	0		L
Average:	5.9											L
Analysis:												