Canadian	latural	PRESSURE VISUAL INS REPORT		Inspect	Date: Page:	56960-MD-09 10/16/2012 1 of 15 156960	
Criticality Designation		Yelle	W	_			
Insp. Comp: Matrix_Ins Location: 01-24-096 Jurisdiction #: A0146 CRN #: D 319	Grande Prairie - No N/A V-301A N/A	V-301A S		Field: Chincaga LSD: 01-24-096-05V Serial #: 79-087-05A Year Built: 1980			
Manufacturer: KML Manufact	X	quipment Description	n: Other: Gas De				
Status:Out of ServiceMAWP Shell:8619kPaMAWP Tube:MDMT:-20 °FSupportSkirt	ⓐ <u>@ 343 °C</u>	Equip. Type: Vessel: Tower Volume: N/A Height/Length: 8992 mm Size/Diameter.: 1677 mm I.D. on Original CNRL Inventory List: X Y					
			J.E.: <u>1.00</u> Re	,	ube Side	Chall Cida	
Component 1 Main - Shell 2 Top - Head 3 Bottom - Head 4 -	Material SA-516-70 SA-516-70 SA-516-70	Nominal Thk 88.500 mm 69.270 mm 69.270 mm	Diameter 1677.000 mm 1677.000 mm 1677.000 mm 1677.000 mm	OD/ID ID ID ID		Shell Side	
5 -							
Maximum Design Pressure: 9-							
PSV –1 Tag #: <u>N</u> /A	Serial #:			CRN: N			
Model #: N/A Manufacturer: N/A Inlet Size & Type: Outlet Size & Type: Carseal Intact: N/A Shell Side / Tube Side:	-	N/A	Service Con Last Service Block Valve: Code S	Date: N	/A //A		
PSV –2 Tag #: Model #: Manufacturer: Inlet Size & Type: Outlet Size & Type: Carseal Intact: Shell Side / Tube Side:	Capacity: 	ervice During Insp.:	Set Pre Service Con Last Service Block Valve: Code S	CRN: essure: npany: e Date: Stamp:			
PSV Comments							
Not applicable							



PRESSURE VESSEL VISUAL INSPECTION REPORT

156960-MD-09 10/16/2012 2 of 15

156960

01-24-096-05W6 A0146908 Matrix_Inspection Insp. Company: LSD: Jurisdiction #: External Inspection Results - VE External Inspection Performed Action Item Action Item Comment NCR Item N/A Condition (Check Status Bar or Press F1 for Help) Integrity Maintenance Nameplate Legible and broken rivet \boxtimes Accept Foundation and Supports Accept Welded skirt anchored to skid \square Anchor Bolts Accept Secure with minor surface corrosion Grounded directly to South side of skirt Grounding Accept \boxtimes Insulation Condition \square Reject Piping cladding damaged and moss growth PSV \boxtimes Not applicable \square Shell Heads & Nozzles Accept Minor surface corrosion through out Metal Surfaces (Paint) Accept Chipped and flaking exposing base metal \boxtimes \boxtimes Aux Equipment Not applicable Cathodic Protection \boxtimes No external anode Alignment Accept Vertical and upright Flange Connections Adequate thread engagement and hardware Accept \boxtimes **Pressure Gauge** No pressure gauge **Temperature Gauge** 2 temp gauges not within range \boxtimes \square Reject Sight Glass \boxtimes No sight glass Ladder / Platform Accept 2 platforms are secure with cages for ladder Leaks No No evidence of leaks Piping from Vessel Π Accept Riser saddle and lug supports for associated piping Previous UT Survey Yes Locations marked, no history provided UT Company: N/A

External Visual Observations

At the time of inspection the dehydrator was not in service and the vessel is tagged out of service

There is a broken rivet on the nameplate

The coating is flaking and chipped throughout exposing the base metal to very minor surface corrosion with no evidence of pitting.

There are two 24" manways on the vessel. The East side manway, hardware and davit arm are in acceptable condition The top head davit arm and pin have been removed

The 0-300 C temperature gauges are not within design temp range and the 0-500 C gauge needle is at the 500 C mark

All platforms and ladders are secure with well supported cages on the ladders

The top 8" inlet piping cladding is damaged and punctured with moss growth at the cladding interface that may result in MIC The outlet/inlet piping has a small section of cladding/insulation removed, the insulation is exposed, discolored and deteriorating which may result in CUI to the piping system

The top platform support beam is bent on the West side

There is mechanical damage noted thru out the surfaces on the shells, (it appears as a tooling marks from erection) There is also mechanical damage on the top head below the paint

A UT corrosion survey was performed at the time of inspection with no significant wall losses recorded.

Recommendations:

Remove/ replace insulation on piping Replace broken rivet Replace temperature gauges as necessary Replace cladding and remove moss and treat area Clean and touch up the coating to aid in the protection against corrosion

If this vessel is to be moved and/or placed into service the lifting lugs and top nozzle should be MT examined as well as ABSA document AB-10 completed



PRESSURE VESSEL **VISUAL INSPECTION** REPORT

Jurisdiction #:

156960-MD-09 10/16/2012 3 of 15 156960

Insp. Company:

Matrix_Inspection

01-24-096-05W6 LSD:

A0146908

Internal Inspection Results – VI N/A (Not Applicable)

Item	N/A	Condition	Comment (Check Status Bar or Press F1 for Help)	NCR	Action Item Integrity	Action Item Maintenance
Shell			No Internal Inspection Carried Out			
Heads	\square		No Internal Inspection Carried Out			
Manway	\square		No Internal Inspection Carried Out			
Gasket Surfaces			No Internal Inspection Carried Out			
Welds	\square		No Internal Inspection Carried Out			
Refractory	\square		No Internal Inspection Carried Out			
Heating Coils			No Internal Inspection Carried Out			
Demister Pad	\square		No Internal Inspection Carried Out			
Vane Pack	\square		No Internal Inspection Carried Out			
Baffles			No Internal Inspection Carried Out			
Trays	\square		No Internal Inspection Carried Out			
Filter	\square		No Internal Inspection Carried Out			
Internal Coating			No Internal Inspection Carried Out			
Tubesheet	\square		No Internal Inspection Carried Out			
Tube Bundle			No Internal Inspection Carried Out			

Internal Visual Observations

No Internal Inspection Carried Out

Recommendations:

No Internal Inspection Carried Out

				PRESSU	RE VESSE	L		Report #: ect Date:	156960-MD-09 10/16/2012
		3		VISUAL	NSPECTIC	DΝ	mspe	Page:	4 of 15
Canadia	n N	atural		REPORT	•		Insp. C	o. Job #:	156960
Insp. Company: Ma	trix_In	spection	LSD:	01-24-096-	05W6	Juriso	diction #:		46908
Firetube Static Data N/A (Not Ap	plicable)							
Diameter: Not Applical		. ,	Nom	Thickness: Not	Applicable			Bend: Not	Applicable
Length: Not Applica				escription: Not					
		Repo	rt#: Not Applica	· ·	ET 🗌	Rep	ort#· Not	Applicable	
Firetube NDE		-	rt#: Not Applica		RT	•		Applicable	
Performed:	PT	-						Applicable	
	ΡI	🗆 керо	rt#: Not Applica		Other	кер		Applicable	
Firetube Inspection Results		-	1						
Item	N/A	Condition	(Che	Commer eck Status Bar or Pre			NCR	Action Item Integrity	Action Item Maintenance
Burner	\boxtimes		No Firetube Ir	nspection Carrie	d Out				
Stack	\boxtimes		No Firetube Ir	nspection Carrie	d Out				
Flange (Throat)	\boxtimes			nspection Carrie					
Tube Sheet	\boxtimes		No Firetube Ir	nspection Carrie	d Out				
Hot Side	\boxtimes		No Firetube Ir	nspection Carrie	d Out				
Miter	\boxtimes		No Firetube Ir	nspection Carrie	d Out				
Return Bend	\square		No Firetube Ir	nspection Carrie	d Out				
Supports	\boxtimes		No Firetube Ir	nspection Carrie	d Out				
Butt Welds	\boxtimes		No Firetube Ir	nspection Carrie	d Out				
Fillet Welds	\boxtimes		No Firetube Ir	nspection Carrie	d Out				
Firetube Visual Observation	s								
		0t							
No Firetube Inspection Ca	arried	Out							
Recommendations:	Recommendations								
	arriad	Out							
	No Firetube Inspection Carried Out								
1									

Canadian Natural	PRESSURE VESSEL VISUAL INSPECTION REPORT	Report #: Inspect Date: Page: Insp. Co. Job #:	156960-MD-09 10/16/2012 5 of 15 156960					
Insp. Company: Matrix_Inspection LSD:	01-24-096-05W6 Juri	sdiction #:	A0146908					
Vessel NDE and Final Summary: UT Report#: NDE Performed: MT Report#: PT Report#:	RT 🗌 Re	port#: port#: port#:						
Maxi-Trak Observations Summary (Summarize inspection re	esults Max 255 Characters):							
Moss growth and damaged insulation on 8" inlet piping	Temp gauges not within range and 500C gauge needle is at 500C							
Maxi-Trak Recommendations Summary (Summarize Recon	nmendations Max 255 Characters):							
Clean and touch up the coating to aid in the protection age Replace temp gauges as required Remove moss and treat area, replace insulation Replace nameplate rivet	ainst corrosion							
Actions Corrected at Time of Inspection: (If actions were correct	ed at the time of Inspection – note the correct	ed actions here.)						
Additional Visual Observations								
No additional visual observations								
Any other safety concerns or observations from associated	equipment: (for example associate	d piping, buildings,	pumps etc)					
No safety concerns noted at the time of inspection								



Insp. Company:

Matrix_Inspection

01-24-096-05W6

Jurisdiction #:

A0146908

156960-MD-09

10/16/2012

6 of 15

156960

Thickness and Remaining Life Evaluation "Must be Completed"

LSD:

MUST BE COMPLETED AND RESOLVED WITH CNRL IMMEDIATELY UPON DISCOVERY OF LOW WALL THICKNESS AREAS

Step 1: Was any thickness measurement location found to be less than (Nominal WT - Corrosion Allowance)?: No

If YES, proceed to Step 2; if NO, proceed to "Crack Evaluation" and "CNRL Criticality Designation".

Step 2: Which component(s) were found below (Nominal WT - Corrosion Allowance)?

Components found below Nom - CA:

Components				
Top - Head				
- Shell				
Bottom - Head				
Bottom - Drain Nozzle				
N/A - N/A				

Perform Steps 3 - 8 for each component with actual thickness less than (Nominal WT - Corrosion Allowance).

Step 3: Describe Location and Extent of Corrosion:

 Components	Location and Extent of Corrosion
N/A - N/A	Not Applicable for this Inspection
N/A - N/A	Not Applicable for this Inspection
N/A - N/A	Not Applicable for this Inspection
N/A - N/A	Not Applicable for this Inspection
N/A - N/A	Not Applicable for this Inspection

Notes:

Circumferential stress values used for nozzle

Step 4:

- For shells and nozzles, calculate minimum required thickness (T-min) as per ASME Section VIII UG-27.
- For heads, calculate minimum required thickness (T-min) as per ASME Section VIII UG-32.

Components	T-Min
Top - Head	2.374
- Shell	1.162
Bottom - Head	2.374
Bottom - Drain Nozzle	0.304
N/A - N/A	N/A



Insp. Company:

Matrix_Inspection

01-24-096-05W6

Jurisdiction #:

A0146908

156960-MD-09

10/16/2012

7 of 15

156960

Thickness and Remaining Life Evaluation (Continued)

Step 5: Is any measured thickness less than calculated minimum required thickness (T-min)? N/A

LSD:

If YES, complete Step 6 If NO, proceed to Step 7..

Step 6: Is nature and extent of pitting acceptable as per API 510? N/A

Step 7: Calculate Remaining Life as per API 510. How? (Find last reading; use nominal thickness if nothing available). Short Term Corrosion Rates and Long Term Corrosion Rates.

Components	Remaining Life (Yrs)
Top - Head	99
- Shell	99
Bottom - Head	99
Bottom - Drain Nozzle	99
N/A - N/A	N/A

Step 8: Contact CNRL Integrity Coordinator to discuss above results.

- Name of CNRL contact: Not Applicable for this Inspection
- Date and time of conversation: Not Applicable for this Inspection

Summary/results of conversation: Not Applicable for this Inspection

Crack Evaluation by Magnetic Particle or Alternative Inspection "Must be Completed"

MUST BE COMPLETED AND RESOLVED WITH CNRL IMMEDIATELY UPON DISCOVERY OF CRACK-LIKE INDICATIONS

Were any indications found to suggest the vessel contained cracks? N/A

If NO, proceed to "CNRL Criticality Designation".

If YES, Contact CNRL Integrity Coordinator to discuss results.

- Name of CNRL contact: Not Applicable for this Inspection
- Date and time of conversation: Not Applicable for this Inspection

Summary/results of conversation: Not Applicable for this Inspection



156960-MD-09 10/16/2012 8 of 15 156960

Insp. Company:

Matrix_Inspection

01-24-096-05W6

Jurisdiction #:

A0146908

CNRL Criticality Evaluation – "MUST BE COMPLETED"

The CNRL In-Service Pressure Vessel Inspector MUST answer all the following questions

LSD:

- 1. Is the vessel fit-for-service? : Yes
- 2. Was the measured thickness less than the calculated minimum required thickness (T-min) for any component?: No
- 3. Were MT indications found?: N/A
- 4. Was the remaining life less than 6 years for sour service vessels or less than 10 years for sweet service vessels?: No
- 5. Were NCR's or Action Items generated as a result of the inspection? : Yes
- 6. Were UT readings below (Nominal WT Corrosion Allowance) found? : No

Information on CNRL Owner User Program - Criticality Designation and Required Review

RED – Vessel Inspection Results are deemed RED if one of the following occurred:

- The measured thickness was less than the calculated minimum required thickness (T-min) for any component.
- MT indications were found.
- The remaining life was calculated to be less than 6 years for sour-service vessels or less than 10 years for sweet-service vessels.

RED inspection reports must be signed off by the CNRL Chief Inspector.

YELLOW – Vessel Inspection Results are deemed YELLOW if one or more of the following occurred:

- The vessel was declared NOT fit-for-service by the 3rd Party In-Service PV Inspector.
- NCR's or Action Items were generated as a result of the inspection.
- UT readings below (Nominal WT Corrosion Allowance) were found.

YELLOW inspection reports must be signed off by the CNRL Pressure Equipment Integrity Coordinator.

GREEN – Vessel Inspection Results are deemed GREEN if <u>all</u> of the following are true:

- The vessel was declared fit-for-service by the 3rd Party In-Service PV Inspector.
- UT readings below (Nominal WT Corrosion Allowance) were NOT found.
- MT indications were NOT found.
- NCR's or Action Items were NOT generated as a result of the VE inspection.

GREEN inspection reports must be signed off by the 3rd Party In-Service Pressure Vessel Inspector.

Critica	lity Designation		Yellow
Vehicle #:	380 Kms:		Inspector (Name): Matthew B Dickinson PESL: 601
Time In:	00:00 Time Out:	00:00 Hrs	Inspector (Signature): API: 39483
Time In:	00:00 Time Out:	00:00 Hrs	CNRL Coordinator (Name):
Personnel:	SJ		CNRL Coordinator (Signature):
Billing Info:	AFE :		(I am in full agreement with report contents)
			(I am in full agreement with report contents)



Equipment Photographs:



01 nameplate



02 broken rivet





03 overview



04 flash corrosion





05 not within range



05 paint deterioration





06 needle @ 500



07 mechanical damage





08 damaged insulation



09 exposed insulation





10 damaged cladding



11 moss growth





12 mechanical damage on support