

Aspire Energy Resources Ltd.

*53 Burnt Lake Crescent
Red Deer, Alberta T4S 0K6
Ph: (403) 314-5422
Fax: (403) 314-1823*

December 16th, 2014

Oilpro

Attn: Bill Foose

Reference: One (1) "Standard Service" 2,500,000 Btu/hr Lineheater Package

Dear Sir;

In accordance with the requested modifications and specifications given in the subject inquiry, Aspire Energy is pleased to offer the following proposal.

We appreciate the opportunity to submit this proposal and look forward to discussing the contents at your earliest convenience. Should you require clarification or additional information, please contact myself at (403) 314 5422.

Best Regards,

Wendell Stenvig

Quotation

B1492 - 01 Rev. 0

To: Oilpro

Phone: (403)

Fax: (403)

Email:

Attn: Bill Foose

Date: December 16th, 2014

We are pleased to submit the following quotation for your consideration. The conditions contained herein shall form an integral part of this quotation.

<u>Item</u>	<u>Qty</u>	<u>Description</u>	<u>Total Price</u>
1.0	1	"Standard Service" 2,500,000 BTU/HR Lineheater Package	\$ 136,520.00

Quote B1492 - 01 Rev.0

1.0 SHELL "Reconditioned"

- 1 60" Diameter x 30'0" Long Shell
30" Diameter x 60" Long Removable Expansion Tank

2.0 COILS (Split Bundle)

Manufactured by Alco Gas and Oil production equipment Ltd. in 1989
Re-certified by Aspire Energy Resources Ltd. in 2014

Coil A

(8) Eight Passes of 4" Sch. 80. Pipe c/w 4" 1500# RFF flanged outer ends
MAWP 2766 Psi @ -20 / 250 F
Constructed with BC, Alberta & Saskatchewan Registration
100% X-ray

Coil B

(4) Four Passes of 4" Sch. 80. Pipe c/w 4" 600# RFF flanged outer ends
MAWP 1300 Psi @ -20 / 250 F
Constructed with BC, Alberta & Saskatchewan Registration
100% X-ray

3.0 FIRETUBES "Reconditioned"

- (1) 20" O.D Firetube. Rated at 2,500,000 BTU/HR c/w stack.
(10,000 flux rate)
- (1) Steel Flame Arrestor c/w Eclipse main and pilot burners

4.0 INSTRUMENTATION

PRV-100 (1) **FISHER 627-R PRESSURE REDUCING VALVE**
1" FNPT connections
5 to 20 psi range
1/4" orifice

PRV-101/2 (2) **BELLOFRAM MODEL T-50 PRESSURE REDUCING VALVES**
5 to 35 psi range

LG-100 (1) **REDLINE TUBULAR GLASS LEVEL GAUGE**
C/w Carbon steel gauge cocks

TI-100 (1) **TREND TEMPERATURE INDICATOR**
TW-100 3" dial, 6" U length
50 to 500 F
C/w 3/4" MNPT x 1/2" FNPT x 6" long 304 SS thermowell

5.0 FUEL GAS SYSTEM

Off-skid supply

6.0 SKID SPECIFICATION

8'0" wide wide x 32' long
10" wide flange main members
c/w Roll ends

BUILDING SPECIFICATION

OPTIONAL

6.0 MATERIAL SPECIFICATIONS

Coils

Flanges	SA-105
Pipe	SA-106 B
Fittings	SA-234-WPB

Threaded Piping

Pipe	SA-106B, Sch. XH
Fittings	SA-105, 3000#

Instrumentation Fittings

Tubing	3/8" 316 SS 0.035" wall Seamless
Fittings	3/8" 316 SS DKlok

7.0 TESTING

Hydrotesting

Coils and piping will be hydrotested to 1.5 times Maximum Allowable Working Pressure as per ASME B31.3

PWHT

Coils	NO
-------	----

XRAY

Coils	100%
-------	------

Magnetic Particle Testing

Firetubes Yes

Ultrasonic Thickness Testing

Coils Yes

8.0 PAINTING AND COATING SPECIFICATIONS

External Surface Preparation	SSPC-SP-3
External Finish	One (1) Shop Coat Grey Enamel
External Insulation	1 1/2" fiberglass c/w Aluminum Cladding.

9.0 DELIVERY

This equipment shall be complete and ready shipment in 3 to 4 weeks ARO

10.0 TERMS AND CONDITIONS

Aspire Energy preferred terms are as follows.

50% invoiced upon receipt of order, due upon receipt of order
50% invoiced upon completion, due prior to removal

GST and any other applicable taxes, levies or duties must be added to the price, including any additional charges added to the price under this agreement. This quotation is open for acceptance for 30 days from the date of submission, pending prior sale.

A 25% restocking charge will apply to any cancelled order.

11.0 OPTION PRICING